

# DRYLAM

SELECTION ♦ SOLUTIONS ♦ SIMPLICITY

Presents a revolutionary breakthrough  
in lamination technology...the Fujipla  
ALM 3220 Automatic Laminator



[www.drylam.com](http://www.drylam.com)

P: 888-633-1973

F: 866-473-0534

10908 Strang Line Rd.

Lenexa, KS 66215

Dry-Lam is taking lamination of On-Demand Digital Prints to a new level. With the Fujipla ALM 3220, laminating of Digital Prints has never been easier! The ALM 3220 will automatically feed, laminate and trim Digital Prints virtually unattended, freeing you to work on other profitable tasks. When coupled with our ASAP film, the ALM 3220 becomes an instant profit-generator for you! Get this amazing machine only from Dry-Lam, America's Leader in Digital On-Demand and Wide Format Printing Lamination.



SELECTION ♦ SOLUTIONS ♦ SIMPLICITY

Presents a revolutionary breakthrough in lamination technology...the Fujijpla ALM 3220 Automatic Laminator

**ALM 3220 Automatic Laminator**

- Small Foot Print – less than 3 sq. ft.
- Portable – locking roller casters
- 115 Volt, 15 amp service with economy mode
- Ultra quick warm up of less than 5 minutes
- Virtually Unattended Operation
- Digital Sheets sizes: 12"x18", 8.5"x11", 11"x17"
- Automatically feeds up to 200 sheets
- Laminates copy paper or as heavy as 130# cover stock
- Automatic two side lamination
- Automatic Flush or Sealed edge trim option
- 1 year parts and labor warranty

**ALM 3220 Exclusive A.S.A.P. Roll Film**

- Perfect for Digital Print technology
- Anti-static properties

**ALM 3220 Exclusive A.S.A.P. Roll Film**

1.5mil, 12.6" x 984 ft, Gloss	1.5mil, 12.6" x 984 ft, Matte
3.0mil, 12.6" x 492 ft, Gloss	3.0mil, 12.6" x 492 ft, Matte
5.0mil, 12.6" x 328 ft, Gloss	5.0mil, 12.6" x 328 ft, Matte
1.2mil, 12.6" x 984 ft, Nylon (One-sided application)	



**ALM Specifications**

<b>Model</b>	ALM3220
<b>Laminating Speed</b>	20"-48"/min.
<b>Temperature Range</b>	170-270°F
<b>Ultra Fast Warm-Up Time</b>	Approximately 5 minutes
<b>Max Laminating Thickness</b>	16mil
<b>Film Thickness</b>	1.2mil (One-sided application), 1.5mil, 3mil, 5mil A.S.A.P. Roll film
<b>Thickness of Objects</b>	3-10mil
<b>Paper Feeding</b>	Capacity: 200 Sheets, Skew-Free Feature, Paper Guide
<b>Applicable Sizes</b>	<b>Letter</b> Paper Size: 8½" x 11" With Margin: 8.74" x 11.24" Without Margin: 8.38" x 10.88" <b>Tabloid</b> Paper Size: 11" x 17" With Margin: 11.24" x 17.24" Without Margin: 10.88" x 16.88" <b>Digital Paper</b> Paper Size: 12" x 18" With Margin: 12.24" x 18.24" Without Margin: 11.88" x 17.88"
<b>Trimming Methods</b>	2 modes – Flush trim or edge seal for all 4 sides of the print
<b>Operation Panel</b>	LCD display for start, stop, temperature, speed, and trim settings
<b>Other Features</b>	Laminated sheet counter, Film tension control, Roller gap lever, Paper thickness adjustment lever, Automatic stop at end of film, Power saving mode, Emergency stop function
<b>Power Consumption</b>	900W
<b>Power Supply</b>	AC 120V (60Hz)
<b>Net Weight</b>	Laminator: 110 Lbs. Stand: 48.5 Lbs.
<b>Included Accessories</b>	Stand with film waste box, Printed operations manual and CD

www.drylam.com

P: 888-633-1973

F: 866-473-0534

10908 Strang Line Rd.

Lenexa, KS 66215

Distributed by: